Technical Data Sheet

RAK Lacquer Thinner

RAK PAINTS

Product description

RAK Lacquer Thinner is a high performance thinner used primarily as a thinner for acrylic, alkyd, 1K lacquer topcoat products. It is specially formulated cleaning spray equipment's and tools.

Typical use

Thinner for 1K Acrylic, alkyd lacquer & similar paint products.

Colours

Clear

Product data

Property	Description
Solids by Volume	0 ± 2 %
Flash point	7C
Density	0.87 kg/l
VOC-EU	805 g/l

The provided data is typical for factory produced products, subject to slight variation depending on colour. All data is valid for mixed paint.

Gloss description: According to RAK Performance Coatings' definition.

Packaging (typical)

RAK Lacquer Thinner

3.6 L and 18 L

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 30 °C

RAK Lacquer Thinner

24 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

RAK Paints LLC, PO Box: 86012, Tel: +971-7-2444036, Fax: +971-7-2446110, Ras Al Khaimah, UAE. www.rakpaints.com

Date of issue: 01 November 2019

Product Code: 80003, Rev 1

Page 1 of 2

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Material Safety Data Sheet (SDS) for this product. For more information, please visit our website at www.rakpaints.com

RAK Lacquer Thinner

Health and safety

During paint application, it is advisable to wear suitable protective guards (PPE). In case of accidental contact with eyes rinse immediately with plenty of water and seek medical advice. In case of inhalation- remove to fresh air, loosen collar and keep patient rested. Get medical treatment. For remove splashes from skin, use soap and water or approved skin cleanser. Flammable material always keeps away from sources of ignition and do not smoke. Ensure sufficient ventilation during application and drying. Do not breathe vapour/spray. Keep container tightly closed and keep out of reach of children. In case of fire - use foam, carbon dioxide or dry chemicals. For more information, refer MSDS.

Disclaimer

The data provided in this sheet is given to the best of our knowledge and based on laboratory testing and practical experience. We cannot guarantee anything but the product since the conditions and methods during application vary. We reserve the right to change the given data without prior notice. The product data sheet supersedes those previously issued.

For more information, contact your local RAK Paints Representative, go to www.rakpaints.com or call +971-7-2444036.

RAK Paints LLC, PO Box: 86012, Tel: +971-7-2444036, Fax: +971-7-2446110, Ras Al Khaimah, UAE. www.rakpaints.com

Date of issue: 01 November 2019

Product Code: 80003, Rev 1

Page 2 of 2

This Technical Data Sheet supersedes those previously issued.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Material Safety Data Sheet (SDS) for this product. For more information, please visit our website at www.rakpaints.com