

RAK Rust Remover

Product description

RAK Rust Remover is a special, safe and effective product used primarily for removing rust with ease from metal and concrete substrate. It is carefully formulated to leave the metal clean, ready to paint, plate and powder coat.

Typical use

Recommended for use on rusted steel or iron. Removes rust from tools, concrete object, engine components, machine parts, fasteners, or any part that can be safely submerged in the liquid.

Colours

Clear

Product data

Property	Description
Solids by Volume	30 ± 2 %
Flash point	NA
Density	0.86 kg/l
VOC-EU	0 g/l

The provided data is typical for factory produced products, subject to slight variation depending on colour.

All data is valid for mixed paint.

Gloss description: According to RAK Performance Coatings' definition.

Packaging (typical)

RAK Rust Remover 0.9 L, 3.6 L

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 30 °C

RAK Rust Remover 24 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

RAK Rust Remover

Health and safety

During paint application, it is advisable to wear suitable protective guards (PPE). In case of accidental contact with eyes rinse immediately with plenty of water and seek medical advice. In case of inhalation- remove to fresh air, loosen collar and keep patient rested. Get medical treatment. For remove splashes from skin, use soap and water or approved skin cleanser. Flammable material always keeps away from sources of ignition and do not smoke. Ensure sufficient ventilation during application and drying. Do not breathe vapour/spray. Keep container tightly closed and keep out of reach of children. In case of fire - use foam, carbon dioxide or dry chemicals. For more information, refer MSDS.

Disclaimer

The data provided in this sheet is given to the best of our knowledge and based on laboratory testing and practical experience. We cannot guarantee anything but the product since the conditions and methods during application vary. We reserve the right to change the given data without prior notice. The product data sheet supersedes those previously issued.

For more information, contact your local RAK Paints Representative, go to www.rakpaints.com or call +971-7-2444036.